

Suppliers of Acceptable Fire Route Signs

CONCORD SIGNS INC.	61 Greensides Avenue Toronto, ON M6G 3P5	Phone: 416-804-2306 Fax: 416-656-6393
DESIGNED GRAF/X	19 Mansion Street Brampton, ON L6S 3C9 <u>Email:</u> dgrafx@rogers.com	Phone: 226-444-8527
DURA SIGNS LTD.	1110 Birchmount Road, #20 Scarborough, ON M1K 5G7	Phone: 416-755-9809 Fax: 416-755-6883
GOTTESMAN SIGNS LTD.	64 Toro Road North York, ON M3J 2A8	Phone: 416-630-8590 Fax: 416-630-9788
JAY KAY SIGNS	6625 Kitimat Road, #56 Mississauga, ON L5N 6J1 <u>Email:</u> jaykaysigns@on.aibn.com	Phone: 905-567-3611 Fax: 905-567-0630
LAMITIC SIGNS LTD.	9714 Winston Churchill Blvd. Norval, ON L0P 1K0	Phone: 416-518-6691 Fax: 905-866-6767
PRECISION SIGNS LTD.	1220 Ellesmere Road, #14 Scarborough, ON M1P 2X5	Phone: 416-291-7090 Fax: 416-291-7102
RDM SIGN GROUP INC.	2319 Dunwin Drive Mississauga, ON L5L 1A3 <u>Email:</u> info@rdmsigns.com	Phone: 905-607-1960 Fax: 905-607-1961
SAFETY MEDIA INC.	10 Meteor Drive Etobicoke, ON M9W 1A4 Website: www.safetymedia.com Email: info@safetymedia.com	Phone: 416-675-6675 Fax: 416-675-6678
THE SIGN DEPARTMENT	2485 Dunwin Drive, #9 Mississauga, ON L5L 1T1 Website: www.thesigndepartment.ca	Phone: 905-820-7744 Fax: 905-820-3236

Installation Requirements for Fire Route Signs

1. Fire route signs shall be permanently mounted on a rigid sign post, pole or building structure.
2. Fire route signs shall be erected at a height of between 1.9 m and 2.5 m as measured from the edge of the travelled portion of the designated route to the bottom edge of the sign.
3. Fire route signs shall be installed at a distance of between 0.3 m and 3 m from the travelled edge of the designated route.
4. Standard fire route signs shall be installed along the route at approximately 30 m intervals or as frequently as is necessary to identify the route in the judgement of the Fire Chief or his designate.
5. Standard sign type FR-8 shall be installed at a 90 degree angle in relation to the edge of the travelled portion of the designated route, in such a manner as to allow both of the sign faces to be visible to traffic.
6. Standard sign type FR-9 when required, shall be installed at a 90 degree angle to the edge of the travelled portion of the designated route and shall be erected between 0.6 m and 3.0 m and 10.0 m from the property line, along the fire route at all vehicular access points.